


WHY CHOOSE iSED TECHNOLOGY OVER MODIFIED WESTERGREN ESR METHODS?



Results within 20 seconds



Walk-away automation



No per-test disposables



Sampling from primary EDTA tube



100 µL aspirated volume

EFFICIENT WORKFLOW:

iSED analyzers produce **results within 20 seconds** after appropriate sample mixing. Truly STAT ESR results are now possible.

Less than 3 seconds of hands-on time per per sample is needed with iSED analyzers. Walkaway automation frees up valuable technologist time and improves laboratory efficiency.

Automation and sampling from the primary tube limits the risk of biohazard exposure to test operators.

An **automated standardized workflow** reduces subjectivity and operator errors. In addition, miniSED and iSED provide more flexibility in terms of barcode label placement.

FASTER METHODOLOGY:

The methodology used by a manufacturer can determine the limitations impacting the accuracy of ESR results. Gravity-based methodologies have the same limitations as the Westergren method and can be affected by environmental and sample variables.

iSED analyzers use photometric rheology to **accurately** measure the intensity of red blood cell aggregation, which occurs in the first phase of the sedimentation process. iSED analysis is performed rapidly in a closed environment, so the sample is not as exposed to environmental variables.

Unlike many modified Westergren methods, iSED analyzers do not require the use of per-test reagents or disposables.

SMALLER SAMPLE:

The advantage of the iSED system is that it requires the **smallest test volume** (up to 500 µL depending on the tube brand being used). **Only 100 µL** is aspirated for testing, making it possible to reuse the tube for other hematology tests. Low volume and pediatric samples can also be easily run.

Modified Westergren methods require higher sample volumes, increasing the potential for QNS errors and making it more difficult to run pediatric samples.

Some modified Westergren methods also require the use of special tubes, increasing workflow complexity and biohazard exposure risk.

ORDERING

ALCOR sales: 401.737.3774
info@alcorscientific.com

SERVICE AND SUPPORT

ALCOR technical support: 401.737.3774
techservice@alcorscientific.com



222-09-020, Rev. 0

iSED®
Product
Comparison



iSED®

Comparison of Modified Westergren Methods





Comparison of Modified Westergren Methods

	iSED®/iSED® ELITE	Diesse Mini-Cube	Diesse Cube 30 Touch	Diesse Ves-Matic Cube 200	Diesse Ves-Matic 5	Diesse Ves-Matic Cube Track	ELITech Microsed®-System	ELITech Mix-Rate® X20	YHLO VISION	YHLO VISION Pro	RR Mechatronics Starrsed ST
Methodology	Photometric rheology (measures RBC aggregation)	Optical infrared sensor (measures RBC sedimentation)	Optical infrared sensor (measures RBC sedimentation)	Optical infrared sensor (measures RBC sedimentation)	Optical infrared sensor (measures RBC sedimentation)	Optical infrared sensor (measures RBC sedimentation)	Optical infrared sensor (measures RBC sedimentation)	Optical infrared photoelectric cell RBC sedimentation	Optical infrared photoelectric cell LED (measures RBC sedimentation)	Optical infrared photoelectric cell LED (measures RBC sedimentation)	Optical infrared LED emitter and receiver (measures RBC sedimentation)
Sample Volume	Aspirated volume: 100 µL Minimum test volume: 500 µL EDTA whole blood	Minimum test volume: 2.0 mL; 500 µL if using BD Microcontainer® or BD Microcontainer® MAP tubes	1.5-4.0 mL EDTA whole blood	1.5-4.0 mL EDTA whole blood	1.5-4.0 mL EDTA whole blood	1.5-4.0 mL EDTA whole blood	Minimum/testing volume: 1.0 or 1.36 mL Must use Excyte ESR tubes	Minimum/testing volume: 1.0 or 1.36mL Must use Excyte ESR tubes	Minimum/test volume: 2.0mL	Minimum volume: 2.0-2.5 mL Test volume: 1.5 mL	Minimum volume: 2.0 mL Test volume: 1.2 mL
Sample Tube Requirements	13x75 mm EDTA tubes with pierceable cap, BD Microcontainer® MAP tubes (refer to iSED® analyzers tube compatibility chart)	13x75 mm EDTA tubes, 500 µL BD Microcontainer® tubes or BD Microcontainer® MAP EDTA tubes	13x75 mm EDTA tubes, 500 µL BD Microcontainer® tubes or BD Microcontainer® MAP EDTA tubes	13x75 mm EDTA tubes	13x75 mm EDTA tubes	13x75 mm EDTA tubes	Must use Excyte® ESR vacuum or Excyte® ESR non-vacuum tubes	Must use Excyte® ESR vacuum or Excyte® ESR non-vacuum tubes	EDTA 12 or 13 mm tube	EDTA 12 or 13 mm tube	EDTA tubes
Sample Stability	4 hr at room temperature; 24 hrs at 2-8°C	4 hr at room temperature; 24 hrs at 2-8°C	4 hr at room temperature; 24 hrs at 2-8°C	4 hr at room temperature; 24 hrs at 2-8°C	4 hr at room temperature; 24 hrs at 2-8°C	4 hr at room temperature; 24 hrs at 2-8°C	4 hr at room temperature; 24 hrs at 2-8°C; vacuum tubes 12 hr at 2-8°C	4 hr at room temperature; 24 hrs at 2-8°C; vacuum tubes 12 hr at 2-8°C	Tested within 4 hrs after collection	Tested within 4 hrs after collection	4 hr at room temperature; 24 hrs at 2-8°C
Throughput	20 sample capacity, 180 samples per hour	1 sample capacity, 12 samples per hour	30 sample positions, 60 samples per hour	190 samples per hour	89 sample positions, 190 samples per hour	95 samples per hour	10 sample capacity, 40 samples per hour	20 sample positions, 80 samples per hour	8-32 sample positions depending on the model • Model A - 24 tests per hour • Model B - 48 tests per hour • Model C - 96 tests per hour	8-32 sample positions depending on the model • Model A - 24 tests per hour • Model B - 48 tests per hour • Model C - 96 tests per hour	24 sample positions • 30 minute method: 36 samples per h • 60 minute method: 24 samples per h
Time to First Result	3 minute mix + 20 seconds; subsequent results available within 20 seconds	20 minutes after 10-12 manual inversions	20 minutes after 8 manual inversions and 20 inversion mixing cycle	19 minutes	28 minutes	22 minutes	30 minutes (optimal result time); 10 minute pre-indication; 15 minute option	30 minutes (optimal result time); 10 minute pre-indication; 15 minute option	20 minutes	Cycle Mode: 20 minutes + 3 minutes mixing Random Mode: 20 minutes after 16 manual inversions	• 30 minute method • 60 minute method
Workflow	<ul style="list-style-type: none"> Random access Continuous sample loading, can prioritize STTs Onboard mixing Internal sample barcode reader No barcode placement restrictions Can use sample tube for other hematology tests Minimal biohazard risk 	<ul style="list-style-type: none"> Random access Samples must be manually inverted 8 times prior to loading Barcode label placement restrictions Minimal biohazard risk 	<ul style="list-style-type: none"> Random access Samples must be manually inverted 8 times prior to loading, and still require onboard mixing Barcode label placement restrictions Minimal biohazard risk 	<ul style="list-style-type: none"> Random access Continuous sample loading Limit to labels on tube TLA (track compatible) Minimal biohazard risk 	<ul style="list-style-type: none"> Random access Continuous sample loading Onboard mixing Limit to labels on tube Minimal biohazard risk 	<ul style="list-style-type: none"> Random access Continuous sample loading Onboard mixing Limit to labels on tube Minimal biohazard risk 	<ul style="list-style-type: none"> Not random access Manual mixing of samples 10-12 inversions Must use Excyte® ESR Vacuum or Excyte® ESR non-vacuum Tubes 	<ul style="list-style-type: none"> Not random access Samples must be manually inverted 8 times prior to loading Must use Excyte® ESR Vacuum or Excyte® ESR non-vacuum Tubes 	<ul style="list-style-type: none"> Not random access Barcode label placement restrictions 	<ul style="list-style-type: none"> Each sample is diluted with 5 mL of Starrsed diluent Must be inverted at least 8 times before placing onboard Sample is transferred to a tube prior to testing 	
Interface Capability	Yes, uni-directional	Yes, bi-directional	Yes, bi-directional	Yes, bi-directional	Yes, bi-directional	Yes, bi-directional	Yes, uni-directional	Yes, uni-directional	Yes, bi-directional	Yes, bi-directional	Yes, bi-directional
Quality Control	SEDTROL® ESR Control <ul style="list-style-type: none"> Human whole blood matrix (Mimics patients) Open Vial Stability: 60 days at room temperature Shelf life: 18 months Online QC program 	ESR-Chex® Control <ul style="list-style-type: none"> Human whole blood matrix Open vial stability: 7 days at room temperature; 95 days refrigerated Shelf Life: 365 days (1 year) Online QC program 	ESR-Chex® Control <ul style="list-style-type: none"> Human whole blood matrix Open vial stability: 7 days at room temperature; 95 days refrigerated Shelf Life: 365 days (1 year) Online QC program 	ESR Control Cube <ul style="list-style-type: none"> Human whole blood matrix Open vial stability: open vial: 95 days 2-30°C; 7 days at 18-30°C Shelf Life: 365 days (1 year) Online QC program 	ESR Control Cube <ul style="list-style-type: none"> Human whole blood matrix Open vial stability: open vial: 95 days 2-30°C; 7 days at 18-30°C Shelf Life: 365 days (1 year) Online QC program 	ESR Control Cube <ul style="list-style-type: none"> Human whole blood matrix Open vial stability: open vial: 95 days 2-30°C; 7 days at 18-30°C Shelf Life: 365 days (1 year) Online QC program 	Accu-Sed® Plus <ul style="list-style-type: none"> Human whole blood matrix Open vial stability: 31 days at room temperature Shelf Life: 365 days (1 year) Online QC program 	Accu-Sed® Plus <ul style="list-style-type: none"> Human whole blood matrix Open vial stability: 31 days at room temperature Shelf Life: 365 days (1 year) Online QC program 	Bio-Rad QC	Bio-Rad QC	Starrsed Control <ul style="list-style-type: none"> Human whole blood matrix Open Vial Shelf Life: 31 days at room temperature Shelf Life: 540 days at room temperature
Routine Maintenance	<ul style="list-style-type: none"> No operator initiated daily maintenance Automatic washing 1x after 15 minutes idle Deep clean after 30 days or 1000 tests No special cleaning required when running QC material 	Routine maintenance is not required as no sample is aspirated and used for testing	Routine maintenance is not required as no sample is aspirated and used for testing	Routine maintenance is not required as no sample is aspirated and used for testing	Routine maintenance is not required as no sample is aspirated and used for testing	Routine maintenance is not required as no sample is aspirated and used for testing	Routine maintenance is not required as no sample is aspirated and used for testing	Routine maintenance is not required as no sample is aspirated and used for testing	Routine maintenance is not required as no sample is aspirated and used for testing	Routine maintenance is not required as no sample is aspirated and used for testing	<ul style="list-style-type: none"> End of day wash, takes 30 minutes Daily, weekly, and monthly maintenance
Required Accessories	<ul style="list-style-type: none"> Test cards iWASH® solution iWASTE® bottles No per-test reagents/disposables required 	<ul style="list-style-type: none"> Test transponder No per-test reagents/disposables required 	<ul style="list-style-type: none"> Test transponder No per-test reagents/disposables required 	<ul style="list-style-type: none"> Test transponder No per-test reagents/disposables required 	<ul style="list-style-type: none"> Test transponder No per-test reagents/disposables required 	<ul style="list-style-type: none"> Test transponder No per-test reagents/disposables required 	<ul style="list-style-type: none"> Excyte® ESR vacuum or Excyte® non-vacuum tubes 	<ul style="list-style-type: none"> Excyte® ESR vacuum or Excyte® non-vacuum tubes 	Test device	Test device	<ul style="list-style-type: none"> Starrsed Diluent Starrsed X-Clean